

Part. R0180

-  **Best Seller**
-  **Standard**
-  **On request**

Tube dimensions

Outside dia.		Thickness	Inside dia.	Thread	D1	D2	H	L	M	Code	N ↓
mm	Poll"	mm	mm	D	mm	mm	mm	mm	mm		
26,9	3/4	1,5	23,9	M12	27	24	6	30	19	63128	3000
30	-	1	28	M10	30	28,4	6	34	19	61606	3000
				M12	30	28,4	6	34	19	63766	3000
33,7	1	1,5	30,7	M12	34	31	6	35	19	63118	3000
38	-	1,5	35	M10	37,5	35,5	9	44	19	68572	5000
				M16	37,5	35,5	9	44	24	63061	5000
42,4	1 1/4	1,5	39,4	M16	44,5	39,6	9	42	24	63071	5000
				M20	44,5	39,6	9	42	30	52691	8000
48,3	1 1/2	1,5	45,3	M16	48	45,5	10	52	24	63081	5000
				M20	48	45,5	10	52	30	58631	8000
		3	42,3	M16	48	42,6	10	52	24	616592	5000
50	-	1,5	47	M10	50	47,5	10,5	56	19	682812	3000
				M12	50	47,5	10,5	56	19	682822	3000
				M14	50	47,5	10,5	56	24	682832	3000
				M16	50	47,5	10,5	56	24	682842	5000
		2	46	M20	50	47,5	10,5	56	30	682852	8000
				M10	50	46,5	10,5	56	19	682862	3000
				M12	50	46,5	10,5	56	19	682872	3000
				M14	50	46,5	10,5	56	24	682882	3000
54	-	2	50	M16	50	46,5	10,5	56	24	682892	5000
				M20	50	46,5	10,5	56	30	682902	8000
		1,5	57,3	M16	54	50,8	10	62	24	647081	5000
				M20	54	50,8	10	62	30	649801	8000
		2	56,3	M16	60	58	10	62	24	65154	5000
				M16	60	58	10	49	24	607241	5000
				M20	60	58	10	62	30	65164	8000
				M16	60	57	10	62	24	65174	5000
2,5	55,3	M20	60	57	10	62	30	65184	8000		
		M16	60	56	10	62	24	65194	5000		
		M20	60	56	10	62	30	65204	8000		
		M14	80	76,5	10,5	90	24	682912	5000		
80	-	2	76	M16	80	76,5	10,5	90	24	682922	5000
				M20	80	76,5	10,5	90	30	682932	8000
				M24	80	76,5	10,5	90	28	682942	8000
				M14	80	74,5	10,5	90	24	682952	5000
		3	74	M16	80	74,5	10,5	90	24	682962	5000
				M20	80	74,5	10,5	90	30	682972	8000
				M24	80	74,5	10,5	90	28	682982	8000


- Material: bushing in reinforced polyamid PA FV (black). Threaded insert in nickel plated brass.
- Packaging: 50 pieces (codes 63128 - 63118: 60 pieces). Version dia. 80 mm: 25 pieces.
- Fmax. = maximum applicable load in static conditions.

Tube dimensions B.S.I.

Outside dia. Inch	Outside dia. mm	Thickness Inch	Thickness mm	Inside dia. mm	Thread D	D1 mm	D2 mm	H mm	L mm	M mm	Code	Fmax. N
1,5"	38,1	0,065"	1,65	34,8	3/8"-16	37,5	35,5	9	44	19	672211	5000
					1/2"-13	37,5	35,5	9	44	19	59191	5000
					5/8"-11	37,5	35,5	9	44	24	59211	5000
2"	50,8	0,065"	1,65	47,5	3/8"-16	50	48,4	10	56	19	672221	5000
					1/2"-13	50	48,4	10	56	19	61681	5000
					5/8"-11	50	48,4	10	56	24	59221	5000
					3/4"-10	50	48,4	10	56	30	59201	8000
					M16	50	48,4	10	56	24	668191	5000

Item code for order = Part. + Code

- Material: bushing in reinforced polyamid PA FV (black). Threaded insert in nickel plated brass.
- Packaging: 50 pieces.
- Fmax. = maximum applicable load in static conditions.



Assembly

Pressure fitted.
Interference fit.

